

# 19 Zoll Server 3 GHZ 1 GB RAM

**BRAKENSIEK®**  
SYSTEMHAUS



**19 inches Rackmount server black 3 GHz 1 GB of dual channel DDRAM 2x160GB HDD RAID**

Non-new

Technical details:

CPU 3 GHz of Pentium 4 (200\*15)

Aopen DVD disk drive

Tape disk drive

Disks disk drive

1 GB of dual channel the GDR RAM

2x160 GB Seagate hard disk

Gigabyte of GA 8KNXP extremist Rev. 2 with the Pentium i875P chip sentence

Specification

Processor Socket 478 for Pentium ® 4 Processor

Chip set Northbridge: Intel ® 875P MCH

Southbridge: Intel ® ICH5R

Integrated Peripherals:

Adaptec Ultra320 SCSI chip

Intel ® CSA interface Gigabit Ethernet controller

GigaRAID controller chip

Realtek ALC658 CODEC

Front Side coach 800 / 533 / 400 MHz FSB

Memory Type: Dual channel the GDR 400 / 333 / 266 ECC support

Max capacity: 4 GB (Please read FAQ for further information)

DIMM slots: 6 \*

\*Note: Through GIGABYTE innovation of supporting 6 DIMMS memory on Intel chipset motherboard. However, due to chipset limitations there wants be a frequency downgrade of memory modules when 6 DIMMs are fully loaded.

Internal I/O Connectors 2 x Serial ATA

2 x SCSI connector

2 x USB 2.0 (Support 4 ports by cable)

1 x S. / P-DIF input / output pin header

1 x FDD

2 x UltraDMA 133/100/66 coach master IDE (For HDDs only)

2 x UltraDMA 100/66 coach master IDE

CD / AUX in

1 x Game port pin header

Expansion slots 1 x AGP Per slot

5 x PCI slots (PCI 2.3 compliant)

1 x DPS slot

Rear Panel I/O 4 x USB 2.0 ports

1 x RJ45 LAN port

1 x LPT port

2 x COM ports

3 x audio ports (Line in / Line out / MIC)

2 x HP / 2 ports (keyboard / Mouse)

Form Factor ATX  
30.5 cm x 24.4 cm

H/W monitoring ITE 8712fa  
System health status can detect and report by BIOS  
Hardware detecting and reporting for case open, power in voltage, CPU voltage, and fan speed.

BIOS 2 x 4 Mbit flash ROM, Award BIOS

Of Other features C.I.A.  
Xpress Install  
Xpress Recovery  
Smart fan  
EasyTune™ 4  
@BIOS  
Q-Flash™  
Multinational Language BIOS

Driver Intel® chipset software installation utility  
Adaptec Ultra320 SCSI driver  
GigaRAID IDE RAID driver  
Intel® RAID Driver  
Intel® PER / in 1000 CT. LAN driver  
REALTEK audio driver  
USB2.0 driver



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MwSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.

Mitglied der

**Brakensiek Systemhaus  
GmbH & Co. KG  
Klönnestraße 94  
D-44143 Dortmund****BRAKENSIEK®**  

---

**SYSTEMHAUS**

Mitglied im

**[www.brakensiek.com](http://www.brakensiek.com)****Tim Brakensiek**

Mitglied des

 **+49(0)231.985-00 10**

Premium Partner

 **+49(0)231.985-2000**