

IBM IntelliStation Z Pro Xitron Harlequin RIP Heidelberg Hercules



IBM IntelliStation Z per Xitron Harlequin RIP

Technical data

Type Work station

Use recommendation large-scale enterprise

Form factor of the product Midi Tower

Width 20 cm

Depth 46 cm

Height 49.2 cm

Weight 20.4 kg

Colour Black

Processor

Type Intel Pentium III Xeon 550 MHz

Installed number 1

Max supported number 2

Data bus speed 100 MHz

Removal ability Expandable

Chip sentence Intel 440GX

Cache memory

Type L2 - pipeline Burst

Installed size 512 KB

RAM

Technology SDRAM - ECC

Form factor DIMM 168-PIN

Enlargement rule max. 512 mb of module

Memory

Floppy disk drive 3.5" 1.44 mb of disk

Optical memories

Type CD-ROM - IDE

Reading speed 40x

Graphics controller

Type AGP - plug-in map

Graphics processor / manufacturer Diamond Fire GL 1

Videomemory SGRAM

Installed size 32 mb / 32 mb (Max)

Max resolution (externally) in 1920 x in 1200 / 24 bits (16.7 million colours)

Supported resolutions VGA (640x480), XGA (1024x768), SVGA (800x600), SXGA (1280x1024)

Supported graphics issue RGB

Audioexit

Type Sound card - ISA - integrates

Signal processor Cirrus Logic CS in 4235

Sound mode In stereo

Product certifications sound Blaster 16 / Per

Network

Data link Protocol Ethernet, Almost Ethernet

Remote administrative protocol DMI 2.0
Product certifications IEEE 802.3, IEEE 802.3U

Enlargement / Konnektivität

Enlargement insertions whole (freely) 2 (1) x from the front accessibly - 5.25" x 1/2H
3 (2) x inside - 3.5" x 1/3H
2 (1) x from the front accessibly - 3.5" x 1/3H
Enlargement slots whole (freely) 2 (1) x processor - slot 2
1 (0) x AGP 2x - full length
5 (4) x PCI - full length
4 (3) x memory - DIMM 168-PIN
1 (1) x PCI/ISA together used - full length
Interfaces 1 x in parallel - IEEE 1284 (EPP/ECP) - D-Sub (DB-25), 25-pole
2 x USB - type USB A, 4-pole
1 x Infrared - IrDA
2 x serial - RS-232C - D-Sub (DB-9), 9-pole
1 x keyboard - generically - mini-German Institute for Standardization (PS/2 type), 6-pole
1 x mouse - generically - mini-German Institute for Standardization (PS/2 type), 6-pole
1 x display / video - VGA - HD D-Sub (HD-15), 15-pole
1 x network - Ethernet 10Base-T / 100Base-TX - RJ-45
1 x audio - line-in - Stereo Jack plug 3.5 mm
1 x audio - Line out - Stereo Jack plug 3.5 mm
1 x microphone - entrance - mono Jack plug 3.5 mm

Electricity supply

Device type Electricity supply
Necessary mains voltage change stream 110/220 V ± 10% (50/60 hertz)
Put achievement 330 watts

Surroundings terms

Min operating temperature 10 °C
Max operating temperature 32 °C
Allowed air humidity in the company 8 - 80%



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MWSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.

Mitglied der

**Brakensiek Systemhaus
GmbH & Co. KG**
Klönnestraße 94
D-44143 Dortmund**BRAKENSIEK®**
SYSTEMHAUS

Mitglied im

**www.brakensiek.com****Tim Brakensiek**

Mitglied des

 **+49(0)231.985-00 10**

Premium Partner

 **+49(0)231.985-2000**