

Linotype Hell Chromagraph S3300 High-End Trommelscanner Typ 3128

BRAKENSIEK®
SYSTEMHAUS



Linotype Hell S3300 Chromagraph high-end drum scanners

Non-new

Type: 3128

Year: 1993

including SilverFast for Chromagraph
including FireWire Kit

The chrome is a graph S3300 drum scanner with repro quality for:

- The images capture color and black and white reflective and transparent originals
- The input of digital data in computer-based image publishing

The operation is done interactively using the program at a LinoColor Apple Macintosh OS 9 workstation or with the SilverFast software on any PC or Mac OSX system.

The scanning can be done in three steps: Overview, prescan and fine scan.

- Overview is a quick scan. The size of the scanned area is defined by the user.
All templates are included in the selected area. The result shown on the monitor is used to define the scan area for the prescan and fine scan.

- Pre-scan is a scan with an average resolution. It is used, which can be either automatically or manually performed.

- Fine-Scan to scan, the liefert the final image data.
The fine scan takes into account the desired resolution and image analysis in the magnification

A work preparation is possible by mounting the template on ChromaMount or an equivalent preparation course.

Special Features:

- Large sample format 50 x 45 cm (Nutzformat)
- Easy recording of the roller
- Rechnergesteuerter scanning
- Automatic Bledenwahl
- Automatic Focusing
- High sampling resolution by point scanning multiplier
- Digital Contrast detail without additional computation time
- Automatic Image Analysis
- Creation of compatible data Scitex

Specifications:

Scanning method: Multiplierabtastung
Scanning aperture: 12 - 400 microns in 38 steps, automatic. Auswahl
Detail contrast (USM): digital
Focus on computer-controlled

Maximum scan speed of 22.5 rev / sec
Scale range: 20% to 2000%
Max Sample Format: 500 mm 450 mm

Max document thickness: 2.0 mm

Standard Interface: SCSI

Dimensions (width * height * depth) 1.86 m * 1.39 m * 0.87 m

Power consumption: 700 W

Securing customer: 16A

Operating tissue layer: 700 kg

Weight per foot: 235 kg

Noise: 55 dB

BRAKENSIEK®
SYSTEMHAUS



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MWSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.

Mitglied der

**Brakensiek Systemhaus
GmbH & Co. KG
Klönnestraße 94
D-44143 Dortmund****BRAKENSIEK®**
SYSTEMHAUS

Mitglied im

**www.brakensiek.com****Tim Brakensiek**

Mitglied des

 **+49(0)231.985-00 10**

Premium Partner

 **+49(0)231.985-2000**