

Zywall 2 WG

BRAKENSIEK®
SYSTEMHAUS



Zywall 2WG

Non-new

- Internet access through 3G networks (HSDPA, UMTS, GPRS, EDGE).
- Dual-band, tri-mode 802.11a/b/g access point for wireless network
- Web-based content filtering services
- High ZyNOSTM ICSA-certified SPI firewall and IPSec VPN Protection
- Configurable 4-Port-LAN/DMZ/WLAN zones
- 3G card support:
 - Huawei E612, E620, E630, ec321, EC360, EC500
 - Novatel EX720, PC720
 - Option GT HSDPA 7.2 Ready
 - Sierra Wireless AC580, AC595, AC850, AC860, AC875, AC880, AC881

Specifications

System Specifications:

Operation mode

- Routing Mode
- Transparent Mode (Bridge)
- NAT (Network Address Translation)
- Dial Backup

Virtual Private Network

- 5 IPSec VPN connections simultaneously
- DES/3DES/AES-Verschlüsselung
- Manual key entry, IKE and PKI (X.509)
- IPSec NAT Traversal
- Xauth User Authentication
- Redundant VPN connection (VPN HA)

Firewall protection

- Transparent Firewall (Bridge mode)
- Stateful Packet Inspection
- DoS and DDoS protection
- Attack Alert and logs in real time

Content Filtering

- Java / ActiveX / Cookie / Proxy Blocking
- URL and Keyword Blocking
- Web Content Filtering

Network

- DHCP-Client/Server/Relay
- PPPoE
- PPTP

System Management

- Web GUI (HTTP, HTTPS)
- Command Line Interface (Console, Telnet, SSH)
- Firmware Upgrade (Web GUI, TFTP / FTP / SFTP)
- Vantage Centralized Network Management

Wireless

- IEEE802.11a/b/g compatible
- MAC filter
- 64/128-bit WEP Encryption
- IEEE802.1x (EAP-MD5/TLS/TTLS/PEAP)
- WPA/WPA-PSK/WPA2/WPA2-PSK
- Roaming
- Configurable output power

Hardware Specifications

- Status LEDs: PWR, LAN / DMZ 1 ~ 4, WAN, AUX, WLAN, CARD
- Power supply: 12 V DC
- Reset Button: Yes / li>
- LAN / DMZ: 4-port switch, 10/100 Mbit / s Auto-MDI/MDIX
- WAN: 10/100 Mbit / s auto MDI / MDIX
- Dial Backup: RS-232 RJ-45 Null Modem Port
- Console: RS-232 RJ-45 port

Physical Specifications

- Dimensions: 220 (W) x 148 (D) x 30.5 (H) mm
- Weight: 517 g

Environmental Specifications

- Operating Temperature: 0 ° C ~ 50 ° C
- Operating humidity: 20% - 95% (no condensation)
- Storage Temperature: -30 ° C ~ 60 ° C
- Storage Humidity: 20% ~ 95% (no condensation)

Certification

- EMC: FCC Part 15 Class B, CE EMC Class B, C-Tick Class B, VCCI Class B
- Safety: CSA International, CE EN60950-1 (UL60950-1, CSA60950-1, EN60950-1, IEC60950-1)
- C-Tick
- VCCI
- Green Product and WEEE compliant

BRAKENSIEK®
SYSTEMHAUS



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MwSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.

Mitglied der

**Brakensiek Systemhaus
GmbH & Co. KG
Klönnestraße 94
D-44143 Dortmund****BRAKENSIEK®**
SYSTEMHAUS

Mitglied im

**www.brakensiek.com****Tim Brakensiek**

Mitglied des

 **+49(0)231.985-0010**

Premium Partner

 **+49(0)231.985-2000**