

IDEAL 7228-06 LT cutting machine



IDEAL 7228-06 LT cutting machine, new

Professional guillotine with hydraulic pressure

Average length 720 mm

Altitude 80/781 MM

Throat depth 720 mm

Narrow cut 20/901 MM

Mains connection 400 V/50 Hz / 3 ~

Engine power

(Continuous recording)

Blade drive 1.5 KW

Saddle drive 0.1 KW

Press Print MIN. 250 daN

MAX. 2000 daN

Dimensions (H x W x D) 1335 X 1305 / 2100 1500 / 1600 2 X 2 MM

Weight 620 KG

MACHINE EQUIPMENT

- Electro-mechanical blade drive
- Hydraulic clamp drive
- Infinitely adjustable clamping pressure (250-2000 daN) with optical indicator LEDs
- Plug-in clamp plate with optical indicator
- Electro-mechanical back gauge with precision spindle drive (speed 53 mm / s)
- Series standard with air table (air nozzles on the front and rear tables)
- Foot pedal for pre-clamping or mechanical cutting
- Optical cutting line indicator with light emitting diodes (LEDs)
- Stainless steel table tops at the front desk and side tables
- High quality HSS blades made of "Solingen steel"
- Material swing cut
- Solid steel blade carrier guided on both sides, adjustable
- Blade depth adjustment
- Additional tables (left and right) available as a stainless steel table top accessories

SAFETY EQUIPMENT

- Series by them in the work area with light barrier
- Transparent safety cover on the rear table
- Patented IDEAL safety drive
- Two-handed operation with and repetitive
 - ° Auto. Knife and clamp return from every position
- Main switch and safety lock with key
- Blade changing device with covered cutting edge
- × 24-volt control
- Stacker angle for aligning stacks of paper
- "GS" test procedure, the accident prevention regulations and safety requirements of the professional association with the European "CE" standards

BACK CONTROL MODULE

- × 40 programs with 36 steps
- Kettenmaßprogrammierung of up to 9 repeat measurements as a program step
- Automatic program sequence - with section on monitoring program and memory mode
- Direct measurement input on numeric keypad

- 3 memory keys for cut sizes (selectable)
- Digital display with 1 / 10 mm accuracy
- "Set" function key for reference
- Electronic hand wheel for manual back gauge with fine adjustment variable speed control
- Pressure switch for quick adjustment of saddle (forward and reverse)
- Automatic Allowance for back-stop shift
- Memory key for repeat cuts (by touch), plus automatic memory
- Paper output function "EJECT", with and without program mode
- Delete (DELETE) and insert ("INSERT") program of possible steps
- Integrated computer (four basic operations)
- Self-diagnosis system with error indication on display
- Reversible mm / inches (in.)



Please only contact us via our registration form and only if you are a business person yourself. Every offer is subject to prior sale and includes your acceptance to our terms & conditions [Terms and conditions \(AGB\)](#). All logos and trademarks on this site are the property of their respective owners.

You will always receive an invoice including tax, which can be paid via wire transfer, in advance or cash. If you register on paypal, you may also pay by charging your paypal account with your credit card. If you are an EU member and you have a validated tax number which can be validated here: [VIES VAT number validation / MwSt.-Informationsaustauschsystem MIAS\) Validierung der MwSt.-Nummer](#) then you pay tax-free. If you are from outside the EU, you can only pay tax-free, if the export is done with the transport company, called 'Schenker'. If you are not using 'Schenker', we cannot guarantee that we will get the export confirmation in time. In that case, you have to pay tax and you get it.



**Brakensiek Systemhaus
GmbH & Co. KG
Klönnestraße 94
D-44143 Dortmund**

www.brakensiek.com

 **+49(0)231.985-00 10**

 **+49(0)231.985-2000**

BRAKENSIEK®
SYSTEMHAUS

Tim Brakensiek